

PROTON Range

UHD Digital Video Isolator



Overview:

- Supports all ASI, SD-SDI, HD-SDI, 3G-SDI and 6G-SDI Formats
- Eliminate Hum and Noise from Digital Video Signals
- Protect Equipment from Ground Voltage
- 1kV and 4kV Breakdown Voltages
- High Performance and Wide Bandwidth Design
- Passive device
- Compact Standalone or Rack Mountable Unit

Application:


- Noise reduction
- Equipment protection
- OB Truck ground protection

DSMB Technology

www.dsmbtech.com
sales@dsmbtech.com.com

Tel (UK): +44 207 183 0697

Tel (US): +1 305 468 4616



PROTON Range

UHD Digital Video Isolator

Description:

The UVIT UHD Digital Video Isolation Transformer provides a solution to the reduction and elimination of hum and noise that can interfere with serial digital video transmission caused by differences in ground potential, especially those above 20 volts, or induced currents in long cable runs.

This common mode noise results in the degradation of the absolute bit timing of high speed digital signals leading to bit errors. These bit errors will at first reduce the quality of the video and data content within the transmission signal but since digital signals do not degrade gracefully but suffer from a cliff effect, the digital signal can be lost altogether. However, the singular most common symptoms of hum in digital signals is intermittent horizontal black streaks. These streaks are often one line in thickness.

Also, these isolators provide crucial protection to video circuits where ground potential differences exist between equipment. Versions with breakdown voltages of 1kV and 4kV are available.


The UVIT Isolation Transformer supports all 6G, 3G, HD, SD and ASI transmission rates. Provision must be made for DC signals such as camera controls which isolation transformers will block. The unit may be used standalone, or incorporated in to a 19" rack using the RPIT16 Universal Rack Mounting Unit.

Ordering Information:

UVIT010B	1-Channel Digital Video Isolator, 1kV Isolation, Standalone
UVIT010R	1-Channel Digital Video Isolator, 1kV Isolation, Rack Mountable
UVIT040B	1-Channel Digital Video Isolator, 4kV Isolation, Standalone
UVIT040R	1-Channel Digital Video Isolator, 4kV Isolation, Rack Mountable
RPIT16	1RU Universal Rack Mounting Unit, 16-Channels for HVIT0x0R

DSMB Technology
www.dsmbtech.com
sales@dsmbtech.com.com

Tel (UK): +44 207 183 0697
Tel (US): +1 305 468 4616



PROTON Range

UHD Digital Video Isolator

Specification:

Model:	UVIT010B	UVIT040B	UVIT010R	UVIT040R
Channels:	1			
Impedance:	75Ω ±2%, unbalanced			
Bandwidth:	100Mb/s to 6Gb/s			
Noise Rejection:	Better than 60dB Common Mode			
Return Loss:	>15dB 270MHz to 1.5GHz; >10dB at 3GHz; >8dB at 6GHz			
Insertion Loss:	Equivalent to 15 metres of Belden 1694A at 6Gb/s			
Isolation Voltage:	1kV	4kV	1kV	4kV
Size:	20mm [0.85"] diameter x 55mm [2.2"] including connectors		20mm [0.85"] diameter x 55mm [2.2"] including connectors Fitted with XLR mounting plate	
Weight:	30g [1.1oz]			
Environmental:	-25 to +55°C [-13 to 131°F] 5% - 95% non-condensing EN55103-1, EN55103, FCC part 15 EN60950			

DSMB Technology

www.dsmbtech.com
sales@dsmbtech.com.com

Tel (UK): +44 207 183 0697
Tel (US): +1 305 468 4616